

## Service Pontoons

- Incredibly tough all-plastic construction
- Versatile and effective central service working platform
- Specifically designed to meet individual customer requirements
- Simple and quick movement of stock and pen during operation
- Useful holding platform for fish transfer/feed lines and other small equipment
- Mooring points for small tender craft

Pontoon Size	315		450	
PE Flotation Pipe	4 x Ø315mm	6 x Ø315mm	4 x Ø450mm	6 x Ø450mm
Gross Buoyancy Per Metre (Kgs)*	320	480	650	975
Length	No limitation to overall length			
Deck Width	1950mm		2970mm	
Overall Width	2200mm		3020mm	
Freeboard	250mm		450mm	
Handrail	Fixed PE/Rope/None			
Hammerhead	Optional/Sizes available upon request			

\*Calculations for seawater conditions  
(Fusion Marine Limited reserves the right to make improvements and changes to products and specifications without notice)

## PONTOON

### Parts - 315 Pontoon

- 1 4 or 6Ø 315mm thick walled polyethylene flotation pipe
- 2 Heavy duty PE base unit
- 3 Electrofusion stops used to minimise base movement
- 4 Ø315mm pontoon support beam designed to sit on top of flotation pipes to create means for a walkway
- 5 Ø50mm retainer pipe used to secure pontoon beams to base units utilising electrofusion process and control
- 6 Slip resistance recycled plastic decking
- 7 Slip resistant deck cover
- 8 Ø125mm PE handrail upright
- 9 Ø28mm rope or Ø125mm sturdy PE handrail
- 10 Stainless steel stanchion support
- 11 6x2m pontoon hammer head
- 12 Stainless steel mooring cleat
- 13 4.3m/5 Tonne red mooring strop

More information available in the Fusion Marine Pontoon Brochure

